



Quotation of Pan & Tile motor								
Feature		Picture	Function	Model no.	Unit price(USD)	Note	Bracket	
Outdoor pan & tile motor								
Input voltage	24V AC 50/60Hz			PT303	34	Default 24V AC AC110V plus 2USD AC220V plus 6USD	Unit price 4.5USD 	
Dimension	Ø190*275(301); Ø200x255(303)		Build in decoder	PT303Q	49			
Rotation angle	Level 350 °Tile ±35°							
Rotation speed	Level 9°/S, Tile 1°/S							
Load	Level 25kg, Tile 12kg							
Working temperature	working temperature -10℃~+55℃		Build in decoder	PT301	34			
Weight	NW: 3.3KG ; GW:4.5KG			PT301Q	49			
Control	RS485							
Outdoor pan & tile motor								
Input voltage	24V AC 50/60Hz,220V AC 50Hz		Build in decoder	PT3050D	73	AC110V plus 2USD	Unit price 4.5USD  	
Dimension	235*181*270mm			PT3050DQ	88			Default 24V AC AC220V plus 6USD
Weight	NW:6.3KG(3050D) ;6.5KG(3050DQ)							
Rotation angle	Level 0~350 °Tile -10~70°							
Rotation speed	Level 4.5°/S, Tile 4.5°/S							
Load	Level:30kg, tile17kg							
working temperature	-10℃~+55℃							
control	RS485							
Outdoor pan & tile motor								
Input voltage	24V AC 50/60Hz,220V AC 50Hz		Intelligent variable speed pan/tilt	PT3050DZ	152	Default 24V AC AC220V plus 6USD	Unit price 4.5USD  	
Dimension	235*181*270mm							
Weight	NW:6.6KG							
Rotation angle	Level 0~360 °Tile -10~70°							
Rotation speed	Level 0~20°/S, Tile 0~5°/S							
Load	Level:30kg, tile17kg							
working temperature	-10℃~+55℃							
control	RS485							
Indoor pan & tile motor								
Input voltage	AC 220V 50/60Hz			PT306	8.8		Unit price 1.8USD 	
Dimension	Φ119mm*115mm(H)							
Weight	NW:0.8KG							
Rotation angle	Level 0~350 °Tile ±60°							
Rotation speed	Level 6°/S							
Load	Level:7kg							
working temperature	-10℃~+55℃							
Indoor pan & tile motor								
Input voltage	AC 24V 50/60Hz		Mini plastic pan & tile motor	PT306L	9.9		Package including Bracket	
Dimension	Φ65mm*65mm(H)							
Weight	NW:0.2KG							
Rotation angle	Level 0~350 °Tile 0~90 °							
Rotation speed	Level 5°/S							
Load	Level:2kg							
working temperature	-10℃~+55℃							
Indoor pan & tile motor								
Input voltage	24VAC 50/60HZ、110VAC 60HZ		Build in decoder	PT3030W	16.7	AC110V plus 2USD	Package including Bracket	
Dimension	246*114*185mm(H)			PT3030WQ	31.5			
Weight	NW:1.1KG							
Rotation angle	Level 0~350 °Tile -5~50 °							
Rotation speed	Level 4.5°/S, Tile 3.8°/S							
Load	Level:7kg,Tile 4kg							
working temperature	-10℃~+55℃							
control	RS485							
outdoor & indoor Intelligent pan & tile motor								
Input voltage	DC12V		Guard	PT322	8.9		Package including Bracket	
Dimension	169.5*87.2mm		Cruise					
Weight			Line scan					
Rotation angle	Level 0~200 °		address code:					
Rotation speed	7 °/S(Low); 10 °(Middle);13 °(Hight)		0~63					
Load	Level:3KG							
waterproof	IP65							
Preset	16							
working temperature	-10℃~+55℃							
control	RS485							

outdoor & indoor Intelligent pan & tile motor							
Input voltage	DC12V		Track learning	PT326	18		Unit price 1.8USD
Dimension	Φ108*111mm(H)		Area covered				
Weight	NW:1.6KG		address code: 0~255				
Rotation angle	Level 0~355 °						
Rotation speed	0~4.8 °/S						
Load	Level:8kg						
waterproof	IP65						
Preset	128						
working temperature	-10℃~+55℃						
control	RS485						

MOQ 10PCs

Price term EXW-Shenzhen

Delivery time 3~5 working days after receipt of payment

Payment Term: 100% T/T in advance, Western Union, PAYPAL

Warranty one year